

NOTE:

CURTAIN CANNOT OCCUPY SPACE BETWEEN THE 2 500SBTP PULLEYS. THIS SPACE MUST REMAIN CLEAR TO ALLOW FOR MOVEMENT OF SANDBAG.

MINIMUM DISTANCE BETWEEN THE THE MODEL 500SBTP PULLEYS IS 4'

SANDBAG SHOULD ONLY BE FILLED WITH ENOUGH SAND TO PROVIDED THE NECESSARY TENSION.

AUTOMATIC DEVICES COMPANY 2121 S. 12TH ST. ALLENTOWN, PA 18103

THIS DRAWING HAS BEEN PREPARED AS A SERVICE TO OUR CUSTOMER AND IS INTENDED ONLY TO BE SUGGESTIVE IN NATURE AND IS NOT TO BE USED AS AN ACTUAL INSTALLATION DRAWING. PREVAILING JOB CONDITIONS AND ACCEPTED PRACTICES MUST BE TAKEN INTO ACCOUNT WHEN THE EQUIPMENT IS INSTALLED.

SCALE NTS	DJL	DRAWN	⊳	SIZE	
SLN		В	10/	DATE	
		APPR(10/13/16		
SHEET		DRAWN BY APPROVED BY	01		
SHEET 1 OF1	500SBTD DE	DESCRIPTION	DEVICE DEA	SANDBAG T	
DWG NO. A-500SBTD-DE-16	500SBTD DEAD-END PULLEY SIDE		DEVICE DEAD-END PULLEY	SANDBAG TENSION WITH	
-DE-16	SIDE		⊳	REV	