VERS-UTIL® 114 SERIES CURTAIN TRACKS





No. 1140 Channel

1' - 8 oz.

16 gauge extruded aluminum, anodized finish. Obtainable in unspliced lengths up to 20'. Must be curved at factory. Minimum radius: 1' 0" (layout dependent). Approximately: 1-1/4" wide x 1-7/8" high.



No. 1131 Single Carrier

2 - 1 oz.

Carrier spacing: 6". Block provides "bumper-to-bumper" action to prevent carrier binding, supported from 2 polyethylene wheels. Plated swivel for free, effortless and quiet curtain movement. Carrier width: Approximately 13/16".



No. 1131-B Single Carrier

2 - 1 oz.

Carrier spacing: 6". Blg provides "bumper-to-bumper" action supporte from 2 nylon-tired ball-bea wheels. Carrier width: Appr (Optional upgra



1142 Master

struction supported from ne wheels. Extension arms provide 12" overlap on bi-parting tracks (6" in front of 6").

Carrier width: Approximately 2-1/2".



No. 1154 Splicing Plate

1 - 3 oz.

Internal aluminum plate for joining track sections. Assures proper track alignment. Channel must be straight at splice.

Approximately: 4" long.



No. 1148 🚨 unation in no Clamo

spacing: 2'0". Adjustable Re on. Bo through center of to any nnel. ly to rigid overhead

Exte track height: Approximately 1-5/8".



No. 1143 Live t

n tired ball-bearing chored to track end. Also end stop.

3" beyond track end.



No. 1145 Tension Floor Pulley

Equipped with 3" nylon tired ball-bearing wheel. Tension spring provides cord tension.

Approximately: 1" long x 3/4" wide x 9" high.



No. 2160 Cord

100' - 1 lb. 10 oz.

Synthetic center and stretch-resistant. For manually operated tracks.

3/16" (No. 4)



No. 1152 Cable

100' - 1 lb. 3 oz.

Wire center. For machine-operated

tracks. 1/8" (No. 4)



No. 1144 Dead End Pulley

1 - 1 lb. 4 oz.

Equipped with 1 nylon tired ball-bearing wheel and 2 steel idlers. Anchored to track end. Also functions as an end stop. Extends 4" beyond track end.