



No. 2801-A (BL) Single Carrier

1 - 7 1/4 oz.

Carrier spacing: 12". Block constructed of plated steel supported from ball-bearing with 2 heavy duty polyethylene wheels. Plated steel for free, effortless curtain movement. Trim chain supplied for curtain trimming. Gate precludes need for removing and rethreading operating cord. Combined carrier and bumper width: Approximately 2". Length from bottom of track to bottom of 5 chain links: Approximately 9-1/4" from bottom of track to bottom of trim chain.



No. 2801-B (BL) Single Carrier

1 - 6.4 oz.

Carrier spacing: 12". Block constructed of plated steel supported from ball-bearing with 2 heavy duty polyethylene wheels. Plated steel for free, effortless curtain movement. Trim chain supplied for curtain trimming. Combined carrier and bumper width: Approximately 2". Length from bottom of track to bottom of 5 chain links: Approximately 9-1/4" high from bottom of track to bottom of trim chain.



No. 2802 (BL) Master Carrier

1 - 9 oz.

Block constructed of plated steel supported from 2 ball-bearings with 4 heavy duty polyethylene wheels and 2 cable clips which clamp cord to carrier.

Carrier width: Approximately 3-1/2". Length from bottom of track to bottom of 5 chain links: Approximately 9-1/4" high from bottom of track to bottom of trim chain.



No. 2802B Master Carrier with brake

1 - 1 lb. 12 oz.

One foot in length and features nylon-tired, ball-bearing wheels. The spring-loaded brake is released by pulling down on an operating line when positioning the carrier. For walk-draw applications only.

No. 2802B4 Master Carrier with brake

1 - 2 lbs. 3 oz.

This custom unit is similar to the 2802B but is 4 feet in length and features nylon-tired, ball-bearing wheels. The spring-loaded brake is released by pulling down on an operating line when positioning the carrier. For walk-draw applications only.



No. 2849 (BL) Neoprene Ball-Bearing Single Carrier

1 - 12 oz.

Block constructed of plated steel supported from 2 sealed and greased neo-prene-tired ball-bearing wheels. Provides quieter operation. No. 2827 Rubber Spacer must be inserted between each carrier. Used with Model 281 & 283-R.

Approximately: 9-1/4" from bottom of track to bottom of trim chain.



No. 2850 (BL) Neoprene Ball-Bearing Master Carrier

1 - 1 lb. 12 oz.

Block constructed of plated steel supported from 4 sealed and greased neo-prene-tired ball-bearing wheels. Used with Model 281 & 283-R.

Approximately: 9-1/4" high from bottom of track to bottom of trim chain.



No. 2851 (BL) Nylon Ball-Bearing Single Carrier

1 - 9 oz.

Block constructed of plated steel supported from 2 nylon-tired ball-bearing wheels. Provides longer service life and easier operation. Used with Model 282 & 283-N.

Approximately: 9-1/4" high from bottom of track to bottom of trim chain.

DISCONTINUED

DISCONTINUED