



No. 2822 Pocket Mounting Bracket for Model 2800 Track

1 - 12 oz.

Steel offset bracket for mounting Model 2800 track to side of ceiling pocket. Projects track approximately 2" from side of pocket. Must be used with Model 2808 Hanging Clamp (not included). Plated steel construction.

4-1/2"L x 2"W

WITE: If using pocket mounting brackets with bi-parting track system, both 2821 & 2822 pocket brackets must be used.

MTE: These brackets are not designed for wall mounted track systems. They do not project enough to allow the curtain to stack without rubbing against the wall.



No. 2823 Ceiling Bracket

1 - 13 oz.

Ceiling Bracket used when it is not possible to drill through track and attach directly to ceiling.

Approximately: 5-1/4" long x 2" wide x 2-3/4" high.



THREADR

1 - 1 lb

Designed to allow suspension of our various track models from tensile rated threaded rod. The bracket is fabricated from hardened steel and has centered hole designed to accept 1/2" threaded rod. Track hanging clamps not included. Dimensions: 3-7/8"H x 1-1/2"W x 3-1/14"L



No. 2814 [BL] Pipe Clamp

1 pr. - 13 oz. For 1-1/4" I.D. Schedule 40 pipe



No. 2815 [BL] Pipe Clamp

1 pr. - 16 oz.

For 1-1/2" I.D. Schedule 40 pipe



No. 2816 [BL] Pipe Clamp

1 pr. - 18 oz.

For 2" I.D. Schedule 40 pipe



No. 2865 (BL) Tension Floor Pulley

1 - 1 lb. 12 oz.

Equipped with 1 oil-impregnated sleeve bearing nylon wheel. Tension spring provides continuous cord tension. Can be either wall or floor mounted. Springloaded latch maintains wheel in uppermost position during installation.

Approximately: 1-1/2" long x 3-1/2" wide x 13" high.



Multi-Purpose Carrier

6" wide x 8-1/4" high

l - 4 lbs.

Nylon-tired ball-bearing wheels. Rated capacity 225 lbs.