SILENT STEEL® 280 SERIES CURTAIN TRACKS





No. 2805 [BL] Adjustable Floor Pulley

1 - 4 lbs. 5 oz.

Equipped with 1 oil-impregnated sleevebearing nylon wheel. Wheel locks in place via threaded axle. Adjustment - 9". Approximately: 3-1/4" long x 5" wide x 13" high.



No. 2866 5" Adjustable Floor Pulleu

1 - 4 lbs. 13 oz.

For manual operation. Equipped with one 5" diameter glass-filled nylon ball-bearing wheel. Wheel locks in place via threaded axle. Adjustment — 7". Approximately: 3" long x 5-1/2" wide x 13" high. Used with Model 282.



No. 2866-A 8" Adjustable Floor Pulley

1 - 9 lbs.

Equipped with one ball-bearing 8" diameter nylon wheel. Wheel locks in place via threaded axle. Adjustment — 8". Approximately: 4" long x 8" wide x 20" high. Used with Model 283-N and Model 283-R.



No. 2825 Rubber Bumper

9 - 1 07

Attaches to No. 2801 Single Carriers. Functions as noise reducer. Not used with Back Pack $^{\circledR}$ guides.



Consider using the Model 28 Rotodraper®



For more information on the Model 28 and 28-A Rotodrapers[®], please see page 73.

Rubber Spacers

For use with Back Pack[®] guides to provide quieter operation. No.2826 (1/8") inserted between carrier and attached Back Pack[®] Guide. No. 2827 (7/16") inserted on other side of Back Pack[®] Guide and between master carrier and adjoining single carrier; also used with Nos. 2849, 2850, 2851, and 2852 carriers. No. 2827-A is used with Model 283-N and Model 283-R tracks. 5/8" hole.

See Page 84 For Photo of Back Pack® Guides. See next page for Diagrams of Back Packs®.



No. 2826 Rubber Spacer

8 - 1 oz.



No. 2827 Rubber Spacer

6 - 1 oz.



No. 2827-A Rubber Spacer 10 - 1 oz.