



## Rotodraper® Pivot Arms



Shown without optional brake

Shown with optional brake

### No. 28 [28-A] Rotodraper®

1 - 4 lbs. 14 oz.

Used with 2800 track channel. Brackets formed of 11 gauge steel. Can support 75 lbs. maximum weight. Two Pipe Clamps supplied (clamps for 1" pipe standard).

Rotodraper® pivot device are used for changing the position of curtains on tormentors, side legs, back-drops and cycloramas. The effect is easily accomplished either by turning the curtain itself or by fastening a towline to the curtain pipe and pulling the tow line until the curtain is in the desired position.

The pivot device is unique because no implement is required to secure the curtain to its proper position. The Rotodraper® is simply installed and easily manipulated to any angle desired including a full 360° turn.

### OPTIONS INCLUDE:

Models 28-A, 17-A, 14-A, and 6-A include an index plate and spring-loaded roller latch which secures the device at 15 degree intervals and helps to prevent accidental rotation.

With the use of a special brake, track-type Rotodrapers® can be secured at any location along the track, helping to prevent accidental movement of the device. Simply by pulling down on the cord, the brake is released and the pivot arm moved. (Obtainable as an option.)



### No. 17 [17-A] Rotodraper®

1 - 4 lbs. 5 oz.

Used with 1700 track channel. Brackets formed of 11 gauge steel. Can support 75 lbs. maximum weight. Two pipe clamps supplied (clamps for 1" pipe standard).

### OUTSTANDING FEATURES:

- SELF-LOCKING BRAKES (Optional on track type Rotodrapers®)  
No. 401 for use with No. 28 Rotodrapers®  
No. 402 for use with all other Rotodrapers®.  
No. 28 and 17 Rotodrapers® incorporate the use of large diameter Kralastic wheels which help prevent climbing and tilting in the track channel.
- TWO C-CLAMPS No. 400 furnished with each Rotodraper® for fitting to each end of the pipe attached to the Rotodraper®. For use with towlines.
- TENSION SPRING composed of 1-3/32" O.D. heavy duty compression spring. Provides necessary friction to secure Rotodraper® in position.
- PIPE CLAMPS furnished with each Rotodraper® to accommodate 1" pipe. 1-1/4", 1-1/2" and 2" pipe clamps also available BUT MUST BE REQUESTED WHEN ORDER PLACED.
- PIPE BATTEN is available in either 1", 1-1/4", or 1-1/2" O.D.. All pipe is Schedule 40. Maximum suggested length of pipe is 8'. Must be ordered separately.
- DIMENSIONS OF Rotodrapers®:  
Standard Units: 13" long x 2-1/4" wide x 9-3/8" high  
For units with locking devices ("A" type) 13" long x 4" wide x 10" high



### No. 6 [6-A] Rotodraper®

1 - 4-1/2 lbs.

Brackets formed of 11 gauge steel. For hanging from pipe with use of U-bolts. Can support 100 lbs. maximum weight. Two pipe clamps supplied (clamps for 1" pipe standard). Two No. 400 C-clamps provided for attachment to pipe ends.